

Canon

YH16x7 KRS



- ***High Performance***
- ***Excellent Style***
- ***Ergonomically Designed Grip***



YH16x7 KRS

●Fast Zoom Speed 2.0 Sec

●16x Zoom Ratio 7mm Wide, M.O.D.=1.0m




●Ergonomic Design for Gripholding on the Shoulder

●Square Sun Shade for Low Flare
●Easy Operation for Optical Filter

●Light Weight =0.9kg

DIMENSIONS




SPECIFICATION

LENS	YH16X7 KRS
Image Format Covered	1/2"
Zoom Ratio/Format	16:1
Range of Focal Length	7.0-112mm
Maximum Focal Aperture	1:1.9 at 7.0-106.4mm 1:2.0 at 112mm
Angular Field of View (degrees)	W 49.1 x 37.8 T 3.3 x 2.5
M.O.D.	1.0m
Object Dimensions at M.O.D.	W 83.3 x 62.5 T 5.3 x 4.0
Size (W x H x L)	148.9 x 95.4 x 151.9mm
Mass	0.9 kg

OPTICAL ACCESSORIES

ITEM (FILTER)	MODEL
Ultra Violet	UV / 82mm
Skylight	Sky / 82mm
ND4	ND4 / 82mm
ND8	ND8 / 82mm
Softon	Sft / 82mm
Cross Screen	Crs / 82mm
Snow Cross	Snw / 82mm
Sunny Cross	Sny / 82mm
Polarized	PL / 82mm

LENS CONTROLLERS FOR YH16x7



#	Unit	Description	CODE
①	FM-12	Flex Focus Module	1824A012
⑤	FM-70	Flex Dual Module	0002T071
⑧	FC-40	Flex Cable	1824A010
⑨	FFC-15	Flex Focus Controller	1824A024
⑩	FFC-200	Flex Focus Controller	1824A014
⑪	FZC-100	Flex Zoom Controller	1824A021
⑮	FPM-77	Focus Positional Servo Module	1824A020
⑯	FPD-400	Focus Positional Demand	1824A018
⑱	ZSD-15M II	Zoom Demand	1824A071
⑲	ZSD-300M	Zoom Demand	1824A067
⑳	ZSG-200M	Zoom Servo Grip	1824A069
㉓	CR-10	Clamper	1824A007
㉔	EC-80	Zoom Extension Cable (8P)	1824A009

Japan

Canon Inc.(Broadcast Equipment Group)

20-2, Kiyohara-Kogyo-Danchi, Utsunomiya-shi,
Tochigi-ken, 321-3292

Tel:+81(0)28-667-8669 Fax:+81(0)28-667-8672

Maximize your Camera's Performance
<http://www.canon.com/bctv/>

Canon

Specifications subject to change without notice